



More than Meets the Eye

Don't be fooled by the discrete elegance of the Infinity Minuette three-piece satellite/subwoofer loud-speaker system. These compact sculptures are also capable of playing the music of your choice with full-bodied, thrilling realism.

The Minuette satellites reproduce the midrange and upper frequencies with a wealth of detail and an open, spacious soundfield, while the specialized subwoofer handles the deep bass foundation with weight and authority.

Together, they form a unique combination of innovative audio engineering and sophisticated furniture design.

Because the human ear cannot locate the source of low frequencies, the Infinity Minuette satellites and subwoofer offer flexibility of placement, for maximum listening pleasure from an attractive, compact system.

For added flexibility, the Minuette Satellites may be placed on a shelf, on a stand or wall-mounted.

Home Theater System

Multi-channel surround sound adds an entirely new dimension to your viewing and listening experience by creating a three-dimensional space with you at the center of the action. The Infinity Minuette Multi-Channel System has been specifically designed to be the straightforward, no-fuss basis for your five-channel home theater theater entertainment.

The quiet elegance of Infinity Minuette MCS blends in effortlessly in any home environment.

INFINITY MINUETTE MCS



SPECIFICATIONS SATELLITES

Frequency Response	200Hz- 20kHz
Crossover Frequency	5kHz
Sensitivity	87dB @ 1 watt, 1 meter
Nominal Impedance	compatible with 8 ohms
Power Rating	Use with amplifiers rated between 15 and 80 watts RMS
Drivers	3 1/2" shielded woofer and 1/2" polycarbonate tweeter with acoustic lens
Cabinet Finish	Black
Dimensions (WxHxD)	119x175x94 mm

SPECIFICATIONS CENTER

Frequency Response	150Hz- 20kHz
Crossover Frequency	5kHz
Sensitivity	87dB @ 1 watt, 1 meter
Nominal Impedance	compatible with 8 ohms
Power Rating	Use with amplifiers rated between 15 and 80 watts RMS
Drivers	3 1/2" shielded woofer (2 pcs) and 1/2" polycar- bonate tweeter with acoustic lens in D'Appolito configuration
Cabinet Finish	Black
Dimensions (WxHxD)	119x175x94 mm

SPECIFICATIONS SUBWOOFER

Frequency Response	40Hz- 150Hz
Sensitivity	90dB @ 2,87 VOLTS, 1 meter
Nominal Impedance	compatible with 8 ohms
Power Rating	Use with amplifiers rated between 20 and 100 watts, RMS/per channel
Drivers	Dual 6 1/2" polypropy- lene coated woofer
Cabinet Finish	Black Pica
Dimensions (WxHxD)	235x394x387 mm

