



### SPECIFICATIONS

#### VERTICAL AMPLIFIER

Sensitivity: 25 mV p-p/cm (63 mV p-p/inch) at front panel input  
250 mV p-p/cm (630 mV p-p/inch) at rear panel input

Frequency Response: 3 Hz to 200 kHz -3 dB or less

Input Impedance: 250 k ohms

Input Capacity: Less than 40 pF at front panel input  
Less than 60 pF at rear panel input

#### HORIZONTAL AMPLIFIER

Sensitivity: 25 mV p-p/cm (63 mV p-p/inch) at front panel input  
250 mV p-p/cm (630 mV p-p/inch) at rear panel input

Frequency Response: 3 Hz to 200 kHz -3 dB or less

Input Impedance: 250 k ohms

Input Capacity: Less than 40 pF at front panel input  
Less than 60 pF at rear panel input

#### SWEEP GENERATOR

Sweep Frequency: 10 Hz to 100 kHz in four steps

Synchronization: Internal (-)

#### OSCILLATOR

Frequency: 1,000 Hz ± 10%

Output Voltage: Max. 1 V RMS

Calibration (TEST): 0.1 V p-p ± 5%

#### INPUT & OUTPUT:

Audio Input (Left & Right), front & rear FM Multipath (V & H)  
Oscillator Output

#### SELECTOR SWITCH:

Test, Wave Form (Left & Right), Stereo Display & FM Multipath

#### GENERAL

Cathode Ray Tube: 3 inches

Semiconductors: 4 FETs, 19 Transistors & 14 Diodes

Power Voltage: AC 110-120 V/220-240 V, 50/60 Hz

Power Consumption: 25 watts

Dimensions: 16-5/16" W, 5-5/32" H, 11-1/32" D

Weight: 17 lbs.

