

FOR CROSLLEY MODEL 62-TA, 62-TC, 62-TD — CHASSIS No. 37

ALIGNMENT PROCEDURE

Preliminary Output Meter Connections To Voice Coil Terminals of Speaker or to Plate of 35L6GT and Cathode of 35Z5GT
 Generator Ground Connections In Series with .001 MFD. Condenser
 Dummy Antenna 400 Ohm Carbon Resistor in Series with Generator Output
 Position of Volume Control Fully On

ALIGNMENT CHART

Step	Signal Generator Frequency Setting	Input	Band Switch	Tuning Cond. Setting	Trimmer Adjusted	Remarks	Location
1	456 Kc.	Antenna	S. B.	Fully open	2nd I-F (2)	Adjust for maximum output.	Tops of I. F. Trans.
1-A	456	Antenna	S. B.	Fully open	1st I-F (2) Wave trap	Adjust for minimum output.	Center Section of 3 Sec. Trimmer.
2	15.3 Mc.	Antenna	S. W.	Fully open	S. W. "OSC"	Adjust for maximum output.	Top of Tuning Condenser
3	15.0 Mc.	Antenna	S. W.	Approx. 15 on dial	S. W. "Ant."	Adjust for maximum output while rocking gang thru signal.	L. H. Section of 3 Sec. Trimmer.
4	1650 Kc.	Antenna	S. B.	Fully open	B. C. "OSC" (front trimmer right end of chassis)	Adjust for maximum output. Gang does not have to tune thru signal.	R. H. Section of 3 Sec. Trimmer.
5	1400 Kc.	Antenna	S. B.	Approx. 1400 on dial	B. C. "ANT"	Adjust for maximum output.	On Cabinet Back.

When aligning the short wave band "OSC" trimmer care must be exercised to see that the circuits are aligned on the correct frequency and not on the image which is approximately 910 kilocycles less as indicated on the dial. To check, increase generator output, tune-in the generator frequency and then tune-in the image frequency which should be weaker than the fundamental and come in approximately 910 kilocycles lower on the dial than the fundamental. If image cannot be tuned in, the "OSC" trimmer is adjusted to the wrong peak. (Correct peak is the second peak on trimmer from the closed position). Repeat original alignment procedure for more accurate adjustments. Always keep signal generator output low as possible to prevent action of A.S.C. circuit.

Socket Voltage is measured @ 117.5 V line

TUBE VOLTAGE CHART

(BETWEEN SOCKET PINS AND B-) WITH 1000 OHM PER VOLT—500 V. RANGE D. C. VOLTMETER

TUBE	FUNCTION	PIN NUMBER							
		1	2	3	4	5	6	7	8
12SK7	R. F. Amp.			0	Neg.	0	76.	40
12SA7	Osc. Mod.			76	76	Neg.	0	Neg.
12SK7	I. F. Amp.			0	Neg.	0	76	76
12SQ7	Det., Etc.		0	0	0	Neg.	16*	0
35L6	B. P. O.			92	76	0	4
35Z5	Rect.					113AC			100

All voltages may vary 10% of values indicated. Neg. indicates Neg. reading on Voltmeter Scale but of too small a value to record accurately.
 * Measured on 100 V. Scale. Power consumption at 117.5 V. line, 30 watts. Drop across Speaker Field—100 V. Current thru Speaker Field—52 M.A.

