



PHONOLA 561/B

CAPACITÀ

RESISTENZE

Nome.	Valore	Tolleranza %	Tensione di prova Volta	Tipo	Nome.	Valore	Toll. %	Watt
C 1	10.000 pf	± 20	1500		R 1	2 M Ω	± 10	1/2
C 2	15 pf	± 20	•	Ag.	R 2	250 Ω	± 10	1/4
C 3	15 pf	± 20	•	Ag.	R 3	50.000 Ω	± 10	1/4
C 4	20 pf	± 10	•	Ag.	R 4	20.000 Ω	± 10	1
C 5	0.1 uf	± 20	•		R 5	100.000 Ω	± 10	1
C 6	0.1 uf	± 20	•		R 6	10.000 Ω	± 10	1/2
C 7	100 pf	± 10	•	Ag.	R 7	0.5 M Ω	± 10	1/4
C 8	450 pf	± 20	•	Ag.	R 8	50.000 Ω	± 10	1/4
C 9	0.1 uf	± 20	•		R 9	200 Ω	± 10	2
C 10	240 pf	± 5	•	Ag.	R 10	50.000 Ω	± 10	1/4
C 11	2 pf	± 5	•	Ag.	R 11	10.000 Ω	± 10	1/4
C 12	240 pf	± 5	•	Ag.	R 12	50.000 Ω	± 10	1
C 13	50.000 pf	± 20	•		R 13	2 M Ω	± 10	1/2
C 14	10.000 pf	± 20	•		R 14	2 M Ω	± 10	1/2
C 15	2000 pf	± 20	3000		R 15	100.000 Ω	± 10	1/2
C 16	2000 pf	± 20	•		R 16	500 Ω	± 10	2
C 17	50.000 pf	± 20	1500		R 17	250.000 Ω	± 10	1/2
C 18	240 pf	± 20	•	Ag.	R 18	1650 Ω	± 10	Ecc. AP.
C 19	25.000 pf	± 20	•		R 19	100.000 Ω	± 10	1/2
C 20	50 pf	± 10	•	Ag.	R 20	100.000 Ω	± 10	1/2
C 21	240 pf	± 10	•	Ag.				
C 22	200 pf	± 10	•	Ag.				
C 23	100 pf	± 10	•	Ag.				
C 24	10 uf	+ 30 - 20	30	G 1263				
C 25	10.000 pf	± 10	1500					
C 26	500 pf	± 20	•					
C 27	8 uf	+ 30 - 20	500	G 2900				
C 28	8 uf	+ 30 - 20	500	G 2900				
C 29	25.000 pf	± 20	1500					
C 30	0.05 uf	± 20	•					
C 31	10.000 pf	± 20	•					
C 32	2000 pf	± 20	3000					
C 33	8 uf	+ 30 - 20	500	G 2900				
C 34	10.000 pf	± 10	1500					
C 35	20 pf	± 10	•	Ag.				
C 36	10 pf	± 10	•	Ag.				

RV. — Reg volume 1MΩ E con interr.

RT. — Reg. tono 250.000 Ω speciale.