



No.	OHMS
1	2 MRS
2	1 MRS
3	100K
4	25K
5	250K
6	1 MRS Vol. Over & Sw
7	1/2 MRS
8	250K

RESISTORS	WATTS	No.
1	1/2	R1
2	1/2	R2
3	1/2	R3
4	1/2	R4
5	1/2	R5
6	1/2	R6
7	1/2	R7
8	1/2	R8
9	1/2	R9
10	1/2	R10
11	1/2	R11
12	1/2	R12
13	1/2	R13
14	1/2	R14

OHMS	WATTS	No.
1	1/2	C1
2	1/2	C2
3	1/2	C3
4	1/2	C4
5	1/2	C5
6	1/2	C6
7	1/2	C7
8	1/2	C8
9	1/2	C9
10	1/2	C10
11	1/2	C11
12	1/2	C12
13	1/2	C13
14	1/2	C14
15	1/2	C15
16	1/2	C16
17	1/2	C17

No.	MFDS.
1	.002
2	.02
3	.02
4	.00008
5	.02
6	.02
7	.40 (Elect)
8	.25 (SNL ONLY)
9	.00025
10	.01
11	.00025
12	.01
13	.01
14	.00025
15	.01
16	.01
17	.01

CAPACITORS	VOLTS	No.	MFDS.	VOLTS.
1	500	C1	.01	400
2	400	C2	.02	400
3	400	C3	.02	400
4	400	C4	.01	400
5	400	C5	.02	400
6	400	C6	.02	400
7	400	C7	.40 (Elect)	150
8	400	C8	.25 (SNL ONLY)	25
9	400	C9	.00025	25
10	400	C10	.01	25
11	400	C11	.01	25
12	400	C12	.01	25
13	400	C13	.01	25
14	400	C14	.01	25
15	400	C15	.01	25
16	400	C16	.01	25
17	400	C17	.40 (Elect)	25

NOTE:-
 C7 USED ON MODEL SNL ONLY.
 ON MODEL SN POINT "A" IS
 CONNECTED TO CHASSIS.
 SWITCH-1 IS ON-OFF.
 SWITCH-2 IS A.C.-D.C. & BATTERY.
 SWITCH-2 SHOWN FOR A.C.-D.C.
 IF 455 K.C.
 ON MODEL SN SWITCH, SWITCH 2A NOT USED.

Spiegel, Inc. Model 5N
 Cat. No. Z-7126